

***FIRST LINE* GL 5 GEAR LUBRICANTS**

" The First Line of Defense Against Wear. "

PRODUCT DESCRIPTION:

First Line GL 5 Gear Oils are multi-service EP gear lubricants manufactured from high quality base stocks and superior additive technology. They are recommended for use in gearboxes, manual transmissions, bearings, gear reducers and many other applications where an API Service classification GL 5 gear lubricant is specified.

Specifications: API MT-1, API GL-5, MIL-PRF-2105E, MACK GO-J, PG-2 Limited Slip

Directions: Consult owner' s manual for instructions and correct viscosity grade.

Test	Typical Inspections	
	GL5 80w90	GL5 85w140
Viscosity, CST @ 40C	131.7	330.4
Viscosity, CST @ 100C	13.9	24.9
Viscosity Index, min.	96	95
API Gravity, 60F	27.8	26.0
Flash, COC, C (F)	198 (390)	210 (410)
Pour, C (F)	-26 (-15)	-18 (0)
Color	3.5	3.0

The values shown here are typical of current production. All of them may vary within modest ranges.

Hazards: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.