

FIRST LINE TO-4 TRANSMISSION FLUIDS **10W, 30W, 50W**

" The First Line of Defense Against Wear. "

First Line TO-4 Transmission Fluids are a new generation Allison C-4 and CAT TO-4 transmission fluid. They are designed for power shift transmissions, final drives and hydraulic systems. They provide excellent friction performance, oxidation stability, and elastomer compatibility and wear control.

First Line TO-4 Transmission Fluids will provide longer transmission life than heavy-duty engine oils. In meeting Allison C-4 and Caterpillar TO-4 requirements. First Line TO-4 Transmission Fluids offer improved performance while allowing product consolidation. They are offered in three viscosity grades to meet summer and winter power shift requirements.

Test	Typical Inspections		
	10W	30W	50W
Viscosity, CST @ 40C	38.6	94.6	197.0
Viscosity, CST @ 100C	6.1	10.9	17.6
Viscosity Index	95	95	95
API Gravity, 60F	27.9	27.6	25.6
Color	2.5	4.0	4.0
Pour, C (F)	-29 (-20)	-21 (-5)	-7 (+20)
Flash Point, C	204	232	246

The values shown here are typical of current production. All of them may vary within modest ranges.

Hazards: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.